

Maxxis A/T 980 Bravo has been designed to deliver traction when you need it most.

All-Season, All-Terrain tire designed for excellent off-road performance while retaining the on-road refinement



SPECIFICATIONS

Rim Size	Size	Service Description	SideWall Name	Overall Diameter	Section Width	MaxPSI	Max Load [lbs]	Approved Rim Width [in]	Ply Rating	P/C/LT	Radial/Bias	Tread Depth
15	235/75R15	109S	OWL	28.9	9.3	-	2271	(6)(8)	-	P	RADIAL	13/32
15	30X9.50R15	104S	OWL	29.4	9.5	-	1984	(6.5)(8.5)	6PR	P	RADIAL	17/32
15	31X10.50R15	109S	OWL	30.4	10.5	-	2271	(7)(9)	6PR	LT	RADIAL	17/32
15	32X11.50R15	113R	OWL	31.5	11.5	-	2535	(8)(10)	6PR	P	RADIAL	17/32
15	33X10.50R15	114Q	OWL	32.4	10.5	-	2601	(7)(9)	6PR	LT	RADIAL	17/32
15	33X12.50R15	108Q	OWL	32.4	12.5	-	2205	(8.5)(11)	6PR	LT	RADIAL	17/32
15	35X12.50R15	113Q	OWL	34.5	12.5	-	2535	(8.5)(11)	6PR	LT	RADIAL	17/32
16	235/70R16	106T	OWL	29	9.3	-	2094	(6)(8)	-	P	RADIAL	14/32
16	245/70R16	113/110S	OWL	39.7	9.6	-	2535/2337	(7)(8.5)	8PR	LT	RADIAL	16/32
16	255/70R16	115/112S	OWL	30.3	10.1	-	2649/2469	(6.5)(8)	8PR	LT	RADIAL	16/32
16	265/70R16	117/114S	OWL	30.8	10.6	-	2833/2601	(7)(8.5)	8PR	LT	RADIAL	16/32
16	275/70R16	119/116Q	OWL	31.3	10.8	-	2998/2756	(7)(8.5)	8PR	LT	RADIAL	16/32
16	225/75R16	115/112S	OWL	29.3	8.8	-	2649/2469	(6)(7)	10PR	P	RADIAL	16/32
16	245/75R16	120/116S	OWL	30.5	9.8	-	3086/2756	(6.5)(8)	10PR	LT	RADIAL	16/32
16	265/75R16	123/120Q	OWL	31.7	10.5	-	3417/3086	(7)(8)	10PR	LT	RADIAL	16/32
16	285/75R16	122/119R	OWL	32.8	11.4	-	3307/2998	(7.5)(9)	8PR	LT	RADIAL	17/32

16	235/85R16	120/116S	BSW	31.7	9.3	-	3086/2756	(6)(7.5)	10PR	LT	RADIAL	16/32
17	255/65R17	110S	OWL	30.1	10	-	2337	(7)(9)	-	P	RADIAL	13/32
17	265/65R17	117/114S	OWL	30.6	10.7	-	2833/2601	(7.5)(9.5)	8PR	LT	RADIAL	15/32
17	275/65R17	118/115S	OWL	31.2	11	-	2910/2649	(7.5)(9.5)	8PR	P	RADIAL	15/32
17	225/70R17	110/107S	OWL	29.6	9	-	2337/2149	(6)(7.5)	8PR	LT	RADIAL	16/32
17	245/70R17	119/116S	OWL	30.6	10.7	-	2998/2756	(7.5)(9.5)	10PR	LT	RADIAL	15/32
17	265/70R17	118/115Q	OWL	31.7	10.7	-	2910/2649	(7)(8.5)	8PR	LT	RADIAL	16/32
17	285/70R17	121/118Q	OWL	32.8	11.5	-	3297/2910	(7.5)(9)	8PR	LT	RADIAL	17/32
18	255/60R18	121/109S	-	30.1	10.4	-	3297/2271	-	8PR	LT	RADIAL	13/32
18	265/60R18	114/110S	OWL	30.6	10.8	-	2601/2337	(7.5)(9.5)	8PR	LT	RADIAL	13/32
18	285/60R18	117/114S	OWL	31.5	11.8	-	2833/2601	(8)(10)	8PR	LT	RADIAL	14/32
19	255/55R19	115/112S	BSW	30.2	10.1	-	2649/2469	-	10PR	LT	RADIAL	13/32

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

for Maxxis Tyres | PK
MAXXIS[®]
 CEO | Maxxis Pakistan

A handwritten signature in blue ink is written over a circular blue stamp. The stamp contains the text "AKESHA HARRIAM PVT. LTD." around the perimeter and "Faisalabad" in the center.