


Apply for all-terrain driving, excellent service life, and apply to any axle type vehicle.

Excellent puncture resistance, cutting resistance and tear-resisting



## SPECIFICATIONS

Rim Size	Size	Service Description	SideWall Name	Overall Diameter	Section Width	MaxPSI	Max Load [lbs]	Approved Rim Width [in]	Ply Rating	P/C/LT	Radial/Bias	Tread Depth
12	5.00-12		BSW	23.8	6.1	100	1477	3.5	14	C	BIAS	13
13	5.50-13		BSW	27	7.3	100	1819	4.5	14	C	BIAS	14
13	6.00-13		BSW	25.8	6.7	100	1819	4.5	14	C	BIAS	14
16	6.50-16		BSW	29.5	7.3	177	2150	4.5	10	C	BIAS	14
16	6.50-16		BSW	29.5	7.3	83	2403	4.5	14	C	BIAS	14
16	7.00-16		BSW	30.5	7.9	91	2679	5.5	12	C	BIAS	16
16	7.00-16		BSW	30.7	7.9	106	2911	5.5	14	C	BIAS	16
16	7.00-16		BSW	30.9	7.9	120	3638	5.5	16	C	BIAS	16
16	7.50-16		BSW	31.7	8.5	120	3308	6	14	C	BIAS	17
16	7.50-16		BSW	31.7	8.5	120	3528	6	16	C	BIAS	17
16	8.25-16		BSW	33.7	9.3	91	3749	6.5	14	C	BIAS	19
16	8.25-16		BSW	33.7	9.3	115	4300	6.5	18	C	BIAS	19
20	9.00-20		BSW	40.5	10.1	132	6780	7	18	C	BIAS	22
20	10.00-20		BSW	42	10.9	110	6615	7.5	18	C	BIAS	21
20	11.00-20		BSW	43.5	11.8	132	8048	8	18	C	BIAS	23
20	11.00-20		BSW	43.5	11.8	120	7387	8	20	C	BIAS	23
20	12.00-20		BSW	44.7	12.6	112	7387	8.5	20	C	BIAS	26



Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

for Maxxis Tyres | PK  
**MAXXIS**<sup>®</sup>  
CEO | Maxxis Pakistan

M. 