

C-846 is an exceptionally long life tire due to a special compound. It is suitable for extreme heavy loading due to its strong casing and structure. To provide long life, it has a cut and chip resistant compound with low rolling resistance.



## SPECIFICATIONS

Rim Size	Size	Service Description	SideWall Name	Overall Diameter	Section Width	MaxPSI	Max Load [lbs]	Approved Rim Width [in]	Ply Rating	P/C/LT	Radial/Bias	Tread Depth
13	6.00-13	93/89J	BSW	25.8	6.6	61	1435/1280	4.5	8	LT	BIAS	N/A
14	6.00-14	95/90J	BSW	26.7	6.7	61	1520/1320	4.5	8	LT	BIAS	N/A
14	6.50-14	99/95J	BSW	27.7	7.1	61	1710/1520	4.5	8	LT	BIAS	N/A
14	6.50-14	104/100J	BSW	27.7	7.1	77	1980/1765	4.5	10	LT	BIAS	N/A
15	6.00-15	101/97J	BSW	27.8	6.7	77	1820/1610	4.5	10	LT	BIAS	N/A
15	7.00-15	109/105J	BSW	29.5	7.8	77	2270/2040	5.5	10	LT	BIAS	N/A
15	7.00-15	113/109J	BSW	29.5	7.8	91	2535/2270	5.5	12	LT	BIAS	N/A
15	7.50-15	120/118J	BSW	30.6	8.3	87	3055/2900	6	12	LT	BIAS	N/A
15	7.50-15	121/117J	BSW	30.7	8.3	106	3195/2835	6	14	LT	BIAS	N/A
16	6.00-16	98/94J	BSW	28.7	6.7	61	1655/1475	4.5	8	LT	BIAS	N/A
16	6.50-16	107/103J	BSW	29.4	7.3	77	2150/1930	5.5	10	LT	BIAS	N/A
16	7.00-16	111/106J	BSW	30.3	7.8	77	2405/2095	5.5	10	LT	BIAS	N/A
16	7.00-16	115/110J	BSW	30.3	7.8	91	2680/2335	5.5	12	LT	BIAS	N/A
16	7.50-16	120/116J	BSW	31.6	8.3	91	3085/2755	6	12	LT	BIAS	N/A
16	7.50-16	122/118J	BSW	31.5	8.3	106	3305/2910	6	14	LT	BIAS	N/A
16	8.25-16	126/122J	BSW	33.7	9.2	91	3750/3305	6.5	14	LT	BIAS	N/A



Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

for Maxxis Tyres | PK  
**MAXXIS**<sup>®</sup>  
CEO | Maxxis Pakistan

A handwritten signature in blue ink is written over a circular blue stamp. The stamp contains the text "AKESH KARRIAM PVT. LTD." around the top edge and "Faisalabad" in the center. There are small stars on either side of the company name.