

C-846 is an exceptionally long life tire due to special compounds. It is suitable for extreme heavy loading due to its strong casing and structure. To provide long life, it has a cut and chip resistant compound with low rolling resistance.



## SPECIFICATIONS

Rim Size	Size	Service Description	SideWall Name	Overall Diameter	Section Width	MaxPSI	Max Load [lbs]	Approved Rim Width [in]	Ply Rating	P/C/LT	Radial/Bias	Tread Depth
20	8.25-20	136/131G	BSW	38.4	9.2	117/107	4940/4300	6.5	14	C	BIAS	N/A
20	9.00-20	141/137G	BSW	40.4	10.3	112/102	5675/5070	7	14	C	BIAS	N/A
20	9.00-20	145/140G	BSW	40.4	10.3	127/117	6390/5510	7	16	C	BIAS	N/A
20	10.00-20	146/144G	BSW	41.7	10.9	115/105	6610/4175	7.5	16	C	BIAS	N/A
20	11.00-20	150/145G	BSW	43.1	11.7	115/105	7390/6395	8	16	C	BIAS	N/A

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

for Maxxis Tyres | PK

**MAXXIS®**

CEO | Maxxis Pakistan

