

Due to its cut and chip resistant compound C8808 is a clear choice for off the road trucks and dumpers.



## SPECIFICATIONS

Rim Size	Size	Service Description	SideWall Name	Overall Diameter	Section Width	MaxPSI	Max Load [lbs]	Approved Rim Width [in]	Ply Rating	P/C/LT	Radial/Bias	Tread Depth
9	21X8-9	N/A	BSW	21.3	7.9	145	4495	6	14	C	BIAS	0.8
10	23X9-10	N/A	BSW	23.4	8.9	130	5540	6.5	14	C	BIAS	0.7
20	8.25-20	N/A	BSW	38.3	9.4	120	10085	6.5	14	C	BIAS	0.9
20	9.00-20	N/A	BSW	40.9	10.2	N/A	N/A	7	16	C	BIAS	N/A
20	10.00-20	N/A	BSW	42.4	11	N/A	N/A	7.5	16	C	BIAS	N/A
20	11.00-20	N/A	BSW	43.5	11.6	N/A	N/A	8	16	C	BIAS	N/A
20	12.00-20	N/A	BSW	45	12.4	N/A	N/A	8.5	18	C	BIAS	N/A

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

for Maxxis Tyres | PK  
**MAXXIS®**  
CEO | Maxxis Pakistan