

C-891 is the ideal balance of safety, performance, and durability. While certain tyres in this range are specifically designed to maximize traction and provide stability in off-road situations, others combine the convenience of all-season performance with the durability of all-terrain handling. Maxxis offers choice, value, and quality.



SPECIFICATIONS

Rim Size	Size	Service Description	SideWall Name	Overall Diameter	Section Width	MaxPSI	Max Load [lbs]	Approved Rim Width [in]	Ply Rating	P/C/LT	Radial/Bias	Tread Depth
20	7.00-20	124/120G	BSW	35.6	7.9	107/97	3525/3085	5.5	12	C	BIAS	N/A
20	8.25-20	136/131G	BSW	38.4	9.3	11/107	4940/4300	6.5	14	C	BIAS	N/A
20	9.00-20	141/137G	BSW	40.2	10.2	112/102	5675/5070	7	14	C	BIAS	N/A
20	9.00-20	145/140G	BSW	40.2	10.2	127/117	6390/5510	7	16	C	BIAS	N/A
20	10.00-20	146/142G	BSW	41.7	11	17/107	6610/5840	7.5	16	C	BIAS	N/A
20	11.00-20	150/145G	BSW	42.9	11.7	115/105	7390/6395	8	16	C	BIAS	N/A
20	11.00-20	153/148G	BSW	42.9	12	132/122	8050/6940	8	18	C	BIAS	N/A
20	12.00-20	154/150G	BSW	44.5	12.4	117/107	8270/7390	8.5	18	C	BIAS	N/A

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

for Maxxis Tyres | PK

MAXXIS®

CEO | Maxxis Pakistan