


The full silica tread compound delivers excellent dry and wet grip. Central ribs give straight-line stability at high speed along with optimal handling.

A standard UHP tire engineered to reduce our carbon footprint, the HP5 was designed to feature the renowned Maxxis handling prowess but with more focus on low rolling resistance technologies. The full silica tread compound and bead filler design help reduce rolling resistance while maximizing ride comfort and wet traction.



## SPECIFICATIONS

Rim Size	Size	Service Description	SideWall Name	Overall Diameter	Section Width	MaxPSI	Max Load [lbs]	Approved Rim Width [in]	Ply Rating	P/C/LT	Radial/Bias	Tread Depth
15	195/55R15	85V	BSW	23.4	7.7	-	1135	7	-	P	RADIAL	10/32
15	195/60R15	88V	BSW	24.2	7.7	-	1235	7	-	P	RADIAL	10/32
15	195/65R15	91V	BSW	25	7.7	-	1356	7	-	P	RADIAL	10/32
16	215/45R16	90V	BSW	23.6	8.5	-	1323	8	-	P	RADIAL	10/32
16	195/50R16	88V	BSW	23.7	7.7	-	1235	7	-	P	RADIAL	10/32
16	205/50R16	91W	BSW	24.1	8.1	-	1356	7.5	-	P	RADIAL	10/32
16	195/55R16	91V	BSW	24.5	7.7	-	1356	7	-	P	RADIAL	10/32
16	205/55R16	94W	BSW	24.9	8.1	-	1477	7.5	-	P	RADIAL	10/32
16	215/55R16	97W	BSW	25.4	8.5	-	1609	7.5	-	P	RADIAL	10/32
16	225/55R16	99W	BSW	25.8	8.9	-	1709	8	-	P	RADIAL	10/32
16	195/60R16	89V	BSW	25.3	7.7	-	1279	7	-	P	RADIAL	10/32
16	205/60R16	96V	BSW	25.7	8.1	-	1565	7.5	-	P	RADIAL	10/32
16	215/60R16	99W	BSW	26.2	8.5	-	1709	7.5	-	P	RADIAL	10/32
16	225/60R16	98V	BSW	26.6	8.9	-	1653	8	-	P	RADIAL	10/32



16	215/65R16	98V	BSW	27	8.5	-	1653	7.5	-	P	RADIAL	10/32
17	215/45R17	91W	BSW	24.6	8.5	-	1356	8	-	P	RADIAL	10/32
17	225/45R17	91W	BSW	25	8.9	-	1356	8.5	-	P	RADIAL	10/32
17	235/45R17	97W	BSW	25.4	9.3	-	1609	9	-	P	RADIAL	10/32
17	245/45R17	99W	BSW	25.7	9.6	-	1709	9	-	P	RADIAL	10/32
17	205/50R17	93W	BSW	25.1	8.1	-	1433	7.5	-	P	RADIAL	10/32
17	215/50R17	95W	BSW	25.4	8.5	-	1521	7.5	-	P	RADIAL	10/32
17	225/50R17	98W	BSW	25.9	8.9	-	1653	8	-	P	RADIAL	10/32
17	235/50R17	96V	BSW	26.3	9.3	-	1565	8.5	-	P	RADIAL	10/32
17	205/55R17	95V	BSW	26	8.1	-	1521	7.5	-	P	RADIAL	10/32
17	215/55R17	98W	BSW	26.4	8.5	-	1653	7.5	-	P	RADIAL	10/32
17	225/55R17	101W	BSW	26.9	8.9	-	1819	8	-	P	RADIAL	10/32
17	235/55R17	103W	BSW	27.2	9.3	-	1929	8.5	-	P	RADIAL	10/32
17	215/60R17	96H	BSW	27.2	8.5	-	1565	7.5	-	P	RADIAL	10/32
17	225/60R17	99V	BSW	27.6	8.9	-	1709	8	-	P	RADIAL	10/32
18	225/40R18	92W	BSW	25	8.9	-	1389	9	-	P	RADIAL	10/32
18	235/40R18	95W	BSW	25.4	9.3	-	1521	9.5	-	P	RADIAL	10/32
18	245/40R18	97W	BSW	25.7	9.6	-	1609	9.5	-	P	RADIAL	10/32
18	225/45R18	95W	BSW	25.9	8.9	-	1521	8.5	-	P	RADIAL	10/32
18	235/45R18	98W	BSW	26.3	9.3	-	1653	9	-	P	RADIAL	10/32
18	245/45R18	100W	BSW	26.6	9.6	-	1764	9	-	P	RADIAL	10/32
18	215/50R18	92V	BSW	26.5	8.5	-	1389	7.5	-	P	RADIAL	10/32
18	215/55R18	99V	BSW	27.3	8.5	-	1709	7.5	-	P	RADIAL	10/32
18	225/55R18	98V	BSW	27.8	8.9	-	1653	8	-	P	RADIAL	10/32
17	225/45R17	91W	BSW	25	8.9	-	1356	8.5	-	P	RADIAL	10/32
17	215/50R17	95W	BSW	25.4	8.5	-	1521	7.5	-	P	RADIAL	10/32

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

for Maxxis Tyres | PK  
**MAXXIS®**  
 CEO | Maxxis Pakistan

