


The HP-600 highway terrain tire was designed for SUV owners who demand more refinement and handling. Employing technology from our ultra-high-performance line, the HP-600 features jointless spiral-wound cap ply construction, minimal squirm tread design, and a compound that provides great traction in both wet and dry weather. The HP-600 also features multi-pitch tread blocks, which work like noise-canceling headphones to minimize perceived pattern noise.



SPECIFICATIONS

Rim Size	Size	Service Description	SideWall Name	Overall Diameter	Section Width	MaxPSI	Max Load [lbs]	Approved Rim Width [in]	Ply Rating	P/C/LT	Radial/Bias	Tread Depth
16	245/70R16	107S	OWL	29.6	10	44	2149	7		P	RADIAL	12/32
18	255/55R18	109V XL	BSW	29	10.2	50	2270	8		P	RADIAL	10/32
15	215/70R15	98S	OWL	26.9	8.7	44	1653	6.5		P	RADIAL	11/32
18	235/60R18	103H	BSW	28.7	9.4	44	1929	7		P	RADIAL	11/32
17	255/60R17	110H XL	BSW	29.1	9.8	50	2337	7.5		P	RADIAL	10/32
15	205/70R15	96H	BSW	26.4	7.9	44	1565	6		P	RADIAL	11/32
15	225/70R15	100H	BSW	27.5	8.8	44	1764	6.5		P	RADIAL	11/32
17	225/55R17	101V	BSW	26.9	8.9	44	1819	7		P	RADIAL	10/32
17	235/60R17	102H	BSW	27.3	9.4	44	1875	7		P	RADIAL	11/32
17	215/55R17	98V	BSW	26.5	8.6	44	1653	7		P	RADIAL	9/32
18	225/65R18	103H	BSW	29.6	8.7	44	1929	6.5		P	RADIAL	9/32
15	225/70R15	100S	OWL	27.5	9.1	44	1764	6.5		P	RADIAL	11/32
17	235/65R17	104H	BSW	29.1	8.9	44	1984	7		P	RADIAL	9/32
16	235/60R16	100V	BSW	27.2	9.1	44	1764	7		P	RADIAL	9/32



16	235/70R16	106H	BSW	29	8.9	44	2094	7		P	RADIAL	11/32
16	215/70R16	100H	BSW	27.9	8.1	44	1764	6.5		P	RADIAL	11/32
17	235/70R17	111H XL	BSW	30.2	9.3	50	2403	7		P	RADIAL	11/32
18	225/55R18	98V	BSW	28.2	9.7	44	1653	7		P	RADIAL	11/32
18	235/55R18	100V	BSW	28.3	9.4	44	1764	7.5		P	RADIAL	11/32
15	255/70R15	108S	OWL	29.1	10.4	44	2205	7.5		P	RADIAL	12/32
18	265/60R18	110S	OWL	30.5	10.7	44	2337	8		P	RADIAL	10/32
17	225/65R17	102H	BSW	28.5	8.6	44	1874	6.5		P	RADIAL	9/32
15	265/70R15	112S	OWL	29.7	10.9	44	2469	8		P	RADIAL	12/32
15	31X10.50R15	109S	OWL	30.3	10.7	50	2270	8.5	6	LT	RADIAL	14/32
18	235/50R18	101V XL	BSW	27.3	9.3	50	1819	7.5		P	RADIAL	10/32
18	255/55R18	109H XL	BSW	29	10.2	50	2270	8		P	RADIAL	10/32
19	245/55R19	103H	BSW	29.7	9.6	44	1929	7.5		P	RADIAL	10/32
16	215/65R16	98H	BSW	27	8.9	44	1653	6.5		P	RADIAL	11/32
16	265/70R16	112S	OWL	30.6	10.7	44	2469	8		P	RADIAL	12/32
15	30X9.50R15	104S	OWL	30	9.8	50	1985	7.5	6	LT	RADIAL	14/32

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

for Maxxis Tyres | PK
MAXXIS[®]
 CEO | Maxxis Pakistan

A handwritten signature in blue ink is written over a circular blue stamp. The stamp contains the text "AKESHA HARRIAM PVT LTD." around the perimeter and "Faisalabad" in the center.