

Rugged trailer radial with robust casing design and proven durability
The M8008 is a high-speed radial constructed tire, providing a smooth ride with extended tread life.



SPECIFICATIONS

Rim Size	Size	Service Description	SideWall Name	Overall Diameter	Section Width	MaxPSI	Max Load [lbs]	Approved Rim Width [in]	Ply Rating	P/C/LT	Radial/Bias	Tread Depth
14	205/75R14		BSW	26.1	8.1	50	1760	5.5	6	P	RADIAL	9/32
15	225/75R15		BSW	28.3	8.9	80	2830	6	10	P	RADIAL	9/32
15	225/75R15		BSW	28.3	8.9	65	2540	6	8	P	RADIAL	9/32
14	205/75R14		BSW	26.1	8.1	35	1430	5.5	4	P	RADIAL	9/32
14	215/75R14		BSW	26.7	8.6	50	1870	6	6	P	RADIAL	9/32
15	205/75R15		BSW	27.1	8.1	50	1820	5.5	6	P	RADIAL	9/32
13	185/80R13		BSW	24.7	7.4	50	1480	5	6	P	RADIAL	9/32
13	175/80R13		BSW	24.1	7.1	50	1360	5	6	P	RADIAL	9/32
15	205/75R15		BSW	27.1	8.1	65	2150	5.5	8	P	RADIAL	9/32
16	235/80R16		BSW	30.8	9.5	80	3420	6.5	10	P	RADIAL	9/32
14	205/75R14		BSW	26.1	8.1	65	2040	5.5	8	P	RADIAL	10/32

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

for Maxxis Tyres | PK
MAXXIS®
CEO | Maxxis Pakistan