

Designed to conquer off-road terrain with ease.

Designed to conquer off-road terrain with ease, the Trepador Bias features a conformable bias-ply casing with an ultra-aggressive sidewall design for excellent off-road traction on sand and rocks. To improve on-road stability and performance, the tyre also features nylon belt reinforcement for extra high-speed stability while improving puncture resistance.



SPECIFICATIONS

Rim Size	Size	Service Description	SideWall Name	Overall Diameter	Section Width	MaxPSI	Max Load [lbs]	Approved Rim Width [in]	Ply Rating	P/C/LT	Radial/Bias	Tread Depth
17	35X12.50-17		BSW	34.6	12.6	45	3000	10	8	LT	BIAS	22/32
20	35X12.50-20		BSW	35.1	12.2	60	3195	10	10	LT	BIAS	22/32
15	35X12.50-15	121L	BSW	35.1	13.2	45	3195	10	8	LT	BIAS	22/32
16	37X12.50-16		BSW	37	13.4	45	3525	10	8	LT	BIAS	23/32
17	40X13.50-17		BSW	40.2	14.3	45	3420	11	8	LT	BIAS	23/32
17	37X13.50-17		BSW	37.3	14.5	60	3750	11	10	LT	BIAS	22/32
17	37X12.50-17		BSW	37.1	13.2	45	3525	10	10	LT	BIAS	23/32
17	42X14.50-17	121L	BSW	42.9	15.3	30	3195	12		LT	BIAS	22/32

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)