

An extreme radial tire that provides maximum traction in any trail condition

Designed for the rigours of high-speed off-roading, the Trepador Radial features high-strength materials in a robust radial design for maximum puncture resistance and high-speed stability. Staggered shoulder blocks and multi-curve siping provide extra traction edges for additional traction bite on difficult terrain.



SPECIFICATIONS

Rim Size	Size	Service Description	SideWall Name	Overall Diameter	Section Width	MaxPSI	Max Load [lbs]	Approved Rim Width [in]	Ply Rating	P/C/LT	Radial/Bias	Tread Depth
18	33X13.00R18	124Q	BSW	33.3	13.1	65	3525			LT	RADIAL	21/32
15	30X9.50R15	104Q	BSW	29.9	9.8	50	1984			LT	RADIAL	20/32
20	33X12.00R20	121Q	BSW	33.2	12.2	65	3200			LT	RADIAL	21/32
15	33X12.50R15	108Q	BSW	32.8	12.4	36	2205			LT	RADIAL	21/32
16	35X12.50R16	121Q	BSW	34.6	13	50	3195			LT	RADIAL	21/32
16	35X12.50-16	120L	BSW	35	13.2	45	3085			LT	BIAS	22/32
15	235/75R15	104/101Q	BSW	29	9.4	50	1984			LT	RADIAL	19/32
17	40X13.50R17	121Q	BSW	39.8	14	35	3195			LT	RADIAL	21/32
18	35X13.00R18	127Q	BSW	34.6	13.1	65	3860			LT	RADIAL	21/32
15	35X12.50R15	113Q	BSW	34.6	13.1	35	2535			LT	RADIAL	21/32
17	35X12.50R17	119Q	BSW	34.6	12.6	50	3000			LT	RADIAL	21/32
17	37X12.50R17	124Q	BSW	36.9	13	50	3525			LT	RADIAL	21/32
15	31X10.50R15	109Q	BSW	30.6	10.8	50	2270			LT	RADIAL	20/32
20	35X13.00R20	121Q	BSW	35	13.1	50	3200			LT	RADIAL	21/32
22	40X15.50R22	127Q	BSW	39.6	14.8	50	3860			LT	RADIAL	21/32

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

for Maxxis Tyres | PK
MAXXIS®
CEO | Maxxis Pakistan

A handwritten signature in blue ink is written over a circular blue stamp. The stamp contains the text "AKESHA HARRIS PVT. LTD." around the top and "Faisalabad" in the center, with two small stars on either side of the company name.