

M-8070 is ideal for sand use.

Ribbed tread specially designed for free rolling

Flat tread profile and highly flexible body cord



## SPECIFICATIONS

Rim Size	Size	Service Description	SideWall Name	Overall Diameter	Section Width	MaxPSI	Max Load [lbs]	Approved Rim Width [in]	Ply Rating	P/C/LT	Radial/Bias	Tread Depth
15	9.00-15		BSW						6	P	BIAS	
16	8.25-16		BSW						8	P	BIAS	
16	9.00-16		BSW						6	P	BIAS	
16	9.00-16		BSW						8	P	BIAS	
17	9.00-17		BSW						8	P	BIAS	
15	8.20-15		BSW	30.2	9.6	45	2205	6	8	P	BIAS	7
15	9.00-15		BSW	33.1	10	45	2465	6	6	P	BIAS	7.2
16	8.25-16		BSW	33.5	9.4	55	2756	6.5	8	P	BIAS	7.2
16	9.00-16		BSW	33.9	10.9	45	2680	8	6	P	BIAS	7.2
16	9.00-16		BSW	33.9	10.9	45	3000	8	8	P	BIAS	7.2
17	8.25-17		BSW	34.8	9.4	50	2910	8	8	P	BIAS	7.2
17	9.00-17		BSW	34.9	11	45	3195	8	8	P	BIAS	7.2
18	9.00-18		BSW	35	10.4	45	2910	8	8	P	BIAS	6.2
20	12.00-20		BSW	45.3	12.8	94	6940	8.5	16	P	BIAS	9.7
15	8.20-15		BSW	30.2	8.6	45	2205	6	8	LT	BIAS	7
15	9.00-15		BSW	33.1	10	45	2465	6	6	LT	BIAS	7
16	8.25-16		BSW	33.5	9.4	55	2756	6.5	8	LT	BIAS	7



16	9.00-16		BSW	33.9	10.9	45	2680	8	6	LT	BIAS	7
16	9.00-16		BSW	33.9	10.9	45	3000	8	8	LT	BIAS	7
17	8.25-17		BSW	34.8	9.4	50	2910	8	8	LT	BIAS	7
17	9.00-17		BSW	34.9	11	45	3195	8	8	LT	BIAS	7
18	9.00-18		BSW	35	10.4	45	2910	8	8	LT	BIAS	6
20	12.00-20		BSW	45.3	12.8	94	6940	8.5	16	LT	BIAS	10

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

for Maxxis Tyres | PK  
**MAXXIS®**  
 CEO | Maxxis Pakistan

A handwritten signature in blue ink is written over a circular blue stamp. The stamp contains the text "AKESHA HARRIAM PVT. LTD." around the perimeter and "Faisalabad" in the center.