

Excellent self-cleaning capacity, durable and strong.

Extra sidewall protector with cut-resistant compound and multi-ply  
Long-wearing and self-cleaning tread design  
Special tread construction and groove, allowing flexibility for rock climbing



## SPECIFICATIONS

Rim Size	Size	Service Description	SideWall Name	Overall Diameter	Section Width	MaxPSI	Max Load [lbs]	Approved Rim Width [in]	Ply Rating	P/C/LT	Radial/Bias	Tread Depth
15	31X11.50-15		BSW						6	P	BIAS	
16	33X11.50-16		BSW	31	11.5	45	2240	8	6	LT	BIAS	16.5/20.8
16	33X13.50-16		BSW	32.5	12.6	30	2210	10	6	LT	BIAS	16.5/20.8
16	33X13.50-16		BSW	32.5	12.6	45	2800	10	8	LT	BIAS	16.5/20.8
15	31X11.50-15		BSW	31	11.5	45	2340	8	6	LT	BIAS	16.5/20.8
15	33X13.50-15		BSW	32.5	13	30	2300	10	6	LT	BIAS	16.5/20.8

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

for Maxxis Tyres | PK

**MAXXIS®**

CEO | Maxxis Pakistan