


Tuff Guard lift tires offer puncture resistance, excellent traction, and long tread life.

Extraordinarily strong casing allows for longer life and lasting wear



SPECIFICATIONS

Rim Size	Size	Service Description	SideWall Name	Overall Diameter	Section Width	MaxPSI	Max Load [lbs]	Approved Rim Width [in]	Ply Rating	P/C/LT	Radial/Bias	Tread Depth
15	2.50-15		BSW	29.2	9.6	135	9446	7.5	16	C	BIAS	26/32
16	7.50-16		BSW	31.7	8.5	115	7995	6	12	C	BIAS	25/32
15	3.00-15		BSW	32.9	11.4	120	13536	8	18	C	BIAS	29/32
15	32X12.10-15		BSW	32.5	12.2	140	15820	9.75	20	C	BIAS	34/32
15	8.25-15		BSW	33.5	9.8	105	8680	6.5	12	C	BIAS	28/32
15	7.50-15		BSW	30.9	8.5	95	6875	6	10	C	BIAS	25/32
15	2.50-15		BSW	29.2	9.6	150	10100	7.5	18	C	BIAS	26/32
15	32X12.10-15		BSW	32.5	12.2	150	16310	9.75	24	C	BIAS	34/32
20	12.00-20		BSW	45.1	13.2	125	19480	8.5	20	C	BIAS	44/32
15	30X8-15		BSW	29.9	8	125	6940	5.5	12	C	BIAS	26/32
15	7.00L-15		BSW	28.9	7.6	145	7495	5.5	14	C	BIAS	26/32
15	8.25-15		BSW	33.5	9.8	135	10175	6.5	16	C	BIAS	28/32
20	10.00-20		BSW	42.5	11.7	115	14910	7.5	16	C	BIAS	40/32
20	12.00-20		BSW	45.1	13.2	100	17095	8.5	16	C	BIAS	44/32
20	12.00-20		BSW	45.1	13.2	150	21670	8.5	24	C	BIAS	44/32
9	6.00-9		BSW	21.7	6.5	150	4130	4	12	C	BIAS	23/32



8	5.00-8		BSW	18.4	5.4	145	3125	3	10	C	BIAS	18/32
15	10.00-15		BSW	35.8	11	115	12290	7.5	16	C	BIAS	30/32
20	10.00-20		BSW	42.5	11.7	100	13740	7.5	14	C	BIAS	40/32
8	5.00-8		BSW	27.8	8.8	140	7530	7	14	C	BIAS	25/32
15	30X8-15		BSW	29.9	8	145	7570	5.5	14	C	BIAS	26/32
15	7.00L-15		BSW	28.9	7.6	125	6870	5.5	12	C	BIAS	26/32
15	28X12.5-15		BSW	27.8	11.6	130	14850	9.75	20	C	BIAS	23/32
16	7.50-16		BSW	31.7	8.5	95	7150	6	10	C	BIAS	25/32
8	5.00-8		BSW	18.4	5.4	115	1830	3	8	C	BIAS	18/32
8	5.00-8		BSW	27.8	8.8	120	6880	7	12	C	BIAS	25/32
15	3.00-15		BSW	32.9	11.4	135	14500	8	20	C	BIAS	29/32
12	7.00-12		BSW	27	7.8	145	6535	5	14	C	BIAS	32/32
15	2.50-15		BSW	29.2	9.6	150	10706	7.5	20	C	BIAS	26/32
10	6.50-10		BSW	23.4	7.2	130	4740	5	12	C	BIAS	30/32
9	6.00-9		BSW	21.7	6.5	125	3715	4	10	C	BIAS	23/32
15	28X12.5-15		BSW	27.8	11.6	140	15565	9.75	24	C	BIAS	23/32
15	8.25-15		BSW	33.5	9.8	120	9385	6.5	14	C	BIAS	28/32
10	6.50-10		BSW	23.4	7.2	115	4225	5	10	C	BIAS	30/32
12	7.00-12		BSW	27	7.8	125	5995	5	12	C	BIAS	32/32
15	7.50-15		BSW	30.9	8.5	115	7690	6	12	C	BIAS	25/32

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

for Maxxis Tyres | PK
MAXXIS[®]
 CEO | Maxxis Pakistan

A handwritten signature in blue ink is written over a circular blue stamp. The stamp contains the text "AKESHA HARRIAN PVT. LTD." around the perimeter and "Faisalabad" in the center.