

A premium tire combining the strength and durability associated with the Maxxis name.



## SPECIFICATIONS

Rim Size	Size	Service Description	SideWall Name	Overall Diameter	Section Width	MaxPSI	Max Load [lbs]	Approved Rim Width [in]	Ply Rating	P/C/LT	Radial/Bias	Tread Depth
16.5	12-16.5		BSW	33.1	12.4	65	5610	9.75	10	P	BIAS	25/32
16.5	12-16.5		BSW	33.1	12.4	50	4810	9.75	8	P	BIAS	25/32
19.5	15-19.5		BSW	40.1	15.2	60	9195	12.5	12	P	BIAS	34/32
16.5	10-16.5		BSW	30.7	10.6	45	3500	8.25	6	P	BIAS	25/32
17.5	14-17.5		BSW	35.8	13.5	80	8550	10.5	14	P	BIAS	33/32
16.5	10-16.5		BSW	30.7	10.6	60	4145	8.25	8	P	BIAS	25/32
17.5	14-17.5		BSW	35.8	13.5	65	7550	10.5	12	P	BIAS	33/32

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

for Maxxis Tyres | PK

**MAXXIS®**

CEO | Maxxis Pakistan