


Double steel-belted construction for long-lasting wear and uniformity.  
Extra heavy-duty sidewall construction delivers responsive handling and performance under demanding commercial applications.



## SPECIFICATIONS

Rim Size	Size	Service Description	SideWall Name	Overall Diameter	Section Width	MaxPSI	Max Load [lbs]	Approved Rim Width [in]	Ply Rating	P/C/LT	Radial/Bias	Tread Depth
14	165/70R14C	89/87R	BSW	23.1	6.5	54	1290	5	6	C	RADIAL	11/32
14	175R14C	99/98R	BSW	25	6.9	65	1709	5	8	C	RADIAL	11/32
15	205/70R15C	106/104R	BSW	26.3	8.2	65	2094	6	8	C	RADIAL	13/32
16	215/75R16C	116/114R	BSW	28.7	8.6	76	2755	6	10	C	RADIAL	13/32
15	215/70R15C	109/107R	BSW	26.9	8.5	65	2270	6.5	8	C	RADIAL	14/32
16	195/60R16C	99/97T	BSW	25.1	8	54	1709	6	6	C	RADIAL	11/32
16	205/75R16C	113/111R	BSW	28.2	8	76	2535	5.5	10	C	RADIAL	13/32
16	195/75R16C	107/105R	BSW	27.5	7.7	69	2150	5.5	8	C	RADIAL	13/32
15	195/70R15C	104/102R	BSW	25.8	7.8	65	1984	6	8	C	RADIAL	13/32
16	235/65R16C	115/113T	BSW	28	9.6	69	2680	7	8	C	RADIAL	13/32
15	225/70R15C	112/110R	BSW	27.4	9.1	65	2469	6.5	8	C	RADIAL	13/32
14	185R14C	102/100R	BSW	25.6	7.5	65	1874	5.5	8	C	RADIAL	11/32
14	195R14C	106/104R	BSW	26.2	7.8	65	2094	5.5	8	C	RADIAL	13/32
16	195/65R16C	104/102T	BSW	26.1	7.9	69	1984	6	8	C	RADIAL	13/32
16	215/65R16C	109/107T	BSW	27	8.7	69	2270	6.5	8	C	RADIAL	13/32
16	205/65R16C	107/105T	BSW	26.5	8.3	69	2149	6	8	C	RADIAL	13/32
15	205/65R15C	102/100T	BSW	25.5	8.3	55	1874	6	6	C	RADIAL	13/32



16	225/65R16C	112/110T	BSW	27.5	9	69	2469	6.5	8	C	RADIAL	13/32
16	225/75R16C	121/120R	BSW	29.4	8.8	84	3195	6	10	C	RADIAL	13/32

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

for Maxxis Tyres | PK  
**MAXXIS®**  
CEO | Maxxis Pakistan



A handwritten signature in blue ink is written over a circular blue stamp. The stamp contains the text "AKESHA HARRIAM PVT. LTD." around the perimeter and "Faisalabad" in the center.