


All season ultra-high performance with premium construction

ALL-SEASON ULTRA HIGH-PERFORMANCE RADIAL With a solid center rib, V-shaped aggressive tread pattern design, and silica tread compound, the MA-Z4S Victra offers superior dry and wet traction, good fuel economy, and excellent handling capability. This unidirectional, ultra-high-performance all-season tire has a low aspect ratio and inch-up sizes. The multiple snow-biting grooves and optimal siping design offer great traction on snowy surfaces.



SPECIFICATIONS

Rim Size	Size	Service Description	SideWall Name	Overall Diameter	Section Width	MaxPSI	Max Load [lbs]	Approved Rim Width [in]	Ply Rating	P/C/LT	Radial/Bias	Tread Depth
17	245/40R17	95W XL	BSW	24.6	9.8	50	1521	NA		P	RADIAL	10/32
16	205/45R16	87W XL	BSW	23.3	8.2	50	1201	NA		P	RADIAL	10/32
17	235/45R17	97W XL	BSW	25.5	9.2	50	1609	NA		P	RADIAL	10/32
15	195/50R15	86V XL	BSW	22.7	7.8	50	1168	NA		P	RADIAL	10/32
17	215/50R17	95W XL	BSW	25.5	8.8	50	1521	NA		P	RADIAL	10/32
17	225/55R17	101W XL	BSW	26.8	9.1	50	1819	NA		P	RADIAL	10/32
18	245/40R18	97W XL	BSW	25.7	9.8	50	1609	NA		P	RADIAL	10/32
17	205/45R17	88W XL	BSW	24.3	8	50	1235	NA		P	RADIAL	10/32
17	215/45R17	91W XL	BSW	24.8	8.3	50	1356	NA		P	RADIAL	10/32
17	205/50R17	93W XL	BSW	25.2	8.3	50	1433	NA		P	RADIAL	10/32
20	255/35R20	97W XL	BSW	27	10	50	1609	NA		P	RADIAL	10/32
15	225/50R15	95V XL	BSW	23.9	9.1	50	1521	NA		P	RADIAL	10/32
16	205/50R16	91V XL	BSW	24.1	8.4	50	1356	NA		P	RADIAL	10/32
20	225/35R20	90W XL	BSW	26.2	9.1	50	1323	NA		P	RADIAL	10/32



15	205/50R15	89V XL	BSW	23.1	8.3	50	1290	NA		P	RADIAL	10/32
17	215/40R17	87W XL	BSW	23.8	8.5	50	1201	NA		P	RADIAL	10/32
18	225/40R18	92W XL	BSW	25.2	9.1	50	1389	NA		P	RADIAL	10/32
17	205/40R17	84W XL	BSW	23.5	8.2	50	1102	NA		P	RADIAL	10/32
16	205/40R16	83W XL	BSW	22.4	8.2	50	1074	NA		P	RADIAL	10/32
16	205/55R16	94V XL	BSW	24.9	8.3	50	1477	NA		P	RADIAL	10/32
17	225/45R17	94W XL	BSW	25.1	8.7	50	1477	NA		P	RADIAL	10/32
16	245/50R16	97V	BSW	25.7	9.8	44	1609	NA		P	RADIAL	10/32
16	215/55R16	97V XL	BSW	25.3	8.8	50	1609	NA		P	RADIAL	10/32
17	225/50R17	98W XL	BSW	25.8	9.1	50	1653	NA		P	RADIAL	10/32
17	255/40R17	98W XL	BSW	25	10.1	50	1653	NA		P	RADIAL	10/32
16	185/55R16	83V	BSW	24	7.3	44	1074	NA		P	RADIAL	10/32
16	195/50R16	88V XL	BSW	23.7	7.8	50	1235	NA		P	RADIAL	10/32
16	225/50R16	96V XL	BSW	25	9.1	50	1565	NA		P	RADIAL	10/32
17	245/45R17	99W XL	BSW	25.7	9.5	50	1709	NA		P	RADIAL	10/32
18	215/35R18	84W XL	BSW	23.9	8.6	50	1102	NA		P	RADIAL	10/32
20	245/35R20	95W XL	BSW	26.9	9.7	50	1521	NA		P	RADIAL	10/32
16	225/55R16	99V XL	BSW	25.8	9.1	50	1709	NA		P	RADIAL	10/32
18	235/40R18	95W XL	BSW	25.5	9.4	50	1521	NA		P	RADIAL	10/32

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

for Maxxis Tyres | PK
MAXXIS[®]
 CEO | Maxxis Pakistan

A handwritten signature in blue ink is written over a circular blue stamp. The stamp contains the text "AKESHA HARRIAM PVT. LTD." around the perimeter and "Faisalabad" in the center.