

The MS800 features a new nano-silica-infused compound combined with environmentally friendly oils that reduce rolling resistance by 11%

New casing design improves road-impact dampening characteristics and enhances ride comfort



## SPECIFICATIONS

Rim Size	Size	Service Description	SideWall Name	Overall Diameter	Section Width	MaxPSI	Max Load [lbs]	Approved Rim Width [in]	Ply Rating	P/C/LT	Radial/Bias	Tread Depth
18	225/40R18	92W	BSW	25	9.1	50	1389	8		P	RADIAL	10/32
15	165/55R15	75V	BSW	22	6.6	44	853	5		P	RADIAL	10/32
17	215/50R17	95V XL	BSW	25.5	8.7	50	1521	7		P	RADIAL	10/32
15	185/55R15	86V XL	BSW	22.9	7.6	50	1168	6		P	RADIAL	10/32
15	215/60R15	94V	BSW	25	8.6	44	1477	6.5		P	RADIAL	10/32
13	175/70R13	82H	BSW	22.6	6.9	44	1047	5		P	RADIAL	9/32
15	175/65R15	84H	BSW	23.6	7	44	1102	5		P	RADIAL	10/32
15	195/60R15	88V	BSW	24.1	8.1	44	1235	6		P	RADIAL	10/32
16	225/55R16	95W	BSW	25.6	9.3	44	1521	7		P	RADIAL	10/32
14	175/65R14	82H	BSW	22.8	7	44	1047	5		P	RADIAL	10/32
15	185/65R15	88H	BSW	24.4	7.5	44	1235	5.5		P	RADIAL	10/32
16	215/60R16	95V	BSW	26	8.9	44	1521	6.5		P	RADIAL	10/32
14	185/65R14	86H	BSW	23.3	7.4	44	1168	5.5		P	RADIAL	10/32
15	185/60R15	84V	BSW	23.8	7.4	44	1102	5.5		P	RADIAL	10/32
16	235/60R16	100V	BSW	27	9.3	44	1764	7		P	RADIAL	10/32
17	225/55R17	97V	BSW	26.7	9.3	44	1609	7		P	RADIAL	10/32
15	205/60R15	91V	BSW	24.6	8.1	44	1356	6		P	RADIAL	10/32
15	205/65R15	95V	BSW	25.4	8.2	44	1521	6		P	RADIAL	10/32

17	235/45R17	97W XL	BSW	25.2	9.5	50	1609	8		P	RADIAL	10/32
14	185/60R14	82V	BSW	22.8	7.4	44	1047	5.5		P	RADIAL	10/32
15	195/65R15	91V	BSW	25	7.8	44	1356	6		P	RADIAL	10/32
15	205/55R15	88V	BSW	23.7	8.1	44	1235	6.5		P	RADIAL	10/32
16	185/55R16	83V	BSW	23.9	7.8	44	1074	6		P	RADIAL	10/32
16	195/55R16	87V	BSW	24.3	7.8	44	1201	6		P	RADIAL	10/32
16	205/55R16	91V	BSW	24.7	8.6	44	1356	6.5		P	RADIAL	10/32
17	215/55R17	94V	BSW	26.3	8.7	44	1477	7		P	RADIAL	10/32
18	245/40R18	97W XL	BSW	25.5	9.6	50	1609	8.5		P	RADIAL	10/32
16	205/60R16	92V	BSW	25.6	8.4	44	1389	6		P	RADIAL	10/32
17	225/50R17	98W XL	BSW	25.7	9.2	50	1653	7		P	RADIAL	10/32
16	225/60R16	98V	BSW	26.6	8.9	44	1653	6.5		P	RADIAL	10/32
14	195/60R14	86V	BSW	23.1	8.1	44	1168	6		P	RADIAL	10/32
15	225/60R15	96V	BSW	25.6	9.1	44	1565	6.5		P	RADIAL	10/32
15	195/65R15	91H	BSW	25	7.8	44	1356	6		P	RADIAL	10/32
16	195/60R16	89V	BSW	25.1	7.9	44	1290	6		P	RADIAL	10/32
16	215/55R16	97V XL	BSW	25.1	8.8	50	1609	7		P	RADIAL	10/32
16	215/65R16	98V	BSW	26.9	8.7	44	1653	6.5		P	RADIAL	10/32
17	225/45R17	94W XL	BSW	24.9	8.8	50	1477	7.5		P	RADIAL	10/32
18	225/45R18	95W	BSW	25.9	8.9	50	1521	7.5		P	RADIAL	10/32
15	195/55R15	85V	BSW	23.3	7.8	44	1135	6		P	RADIAL	10/32
17	205/45R17	84W	BSW	24.3	8.3	44	1102	7		P	RADIAL	10/32
17	215/45R17	91W XL	BSW	24.6	8.4	50	1356	7		P	RADIAL	10/32
18	235/45R18	98W	BSW	26.2	9.3	50	1653	8		P	RADIAL	10/32

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

for Maxxis Tyres | PK  
**MAXXIS**<sup>®</sup>  
 CEO | Maxxis Pakistan

A handwritten signature in blue ink is written over a circular blue stamp. The stamp contains the text "AKESHA HARRIAM PVT. LTD." around the perimeter and "Faisalabad" in the center.