

Championship-winning mud terrain with terrific performance and durability

MUD TERRAIN The Bighorn is a radial construction tire with a wide footprint providing better shock absorption and excellent traction. The Bighorn contains extra large shoulder lugs, protecting the rim and sidewalls from unnecessary cuts and abrasions, while the raised white letters on the sidewall give it a sporty look. Designed to provide a smooth ride suitable for desert, dirt, rock, snow, and mud applications, the Bighorn is suitable for all terrains.



SPECIFICATIONS

Rim Size	Size	Service Description	SideWall Name	Overall Diameter	Section Width	MaxPSI	Max Load [lbs]	Approved Rim Width [in]	Ply Rating	P/C/LT	Radial/Bias	Tread Depth
16	255/85R16	119/116N	BSW	33.3	10.3	65	3000			LT	RADIAL	19/32
16	235/85R16	120/116N	BSW	31.7	9.6	80	3042			LT	RADIAL	19/32
16	285/75R16	122/119M	OWL	33	11.6	65	3305			LT	RADIAL	19/32
16	305/70R16	118/115Q	OWL	33	12.4	50	2910			LT	RADIAL	19/32
15	235/75R15	104/101Q	OWL	29	9.4	50	1984			LT	RADIAL	19/32
18	275/65R18	123/120M	OWL	32.1	11	80	3415			LT	RADIAL	20/32
17	245/70R17	119/116Q	OWL	30.8	9.7	80	3000			LT	RADIAL	19/32
17	275/70R17	120/117Q	OWL	32.3	11	65	3042			LT	RADIAL	19/32
18	325/60R18	124/121Q	OWL	33.3	12.9	65	3525			LT	RADIAL	20/32
15	32X11.50R15	113Q	OWL	31.9	11.6	50	2535			LT	RADIAL	21/32
14	27X8.50R14	95Q	OWL	26.3	8.8	50	1521			LT	RADIAL	19/32
16	265/75R16	123/120M	OWL	31.8	10.6	80	3415			LT	RADIAL	19/32
16	245/75R16	120/116N	OWL	30.6	9.8	80	3042			LT	RADIAL	19/32
17	285/70R17	121/118Q	OWL	33	11.7	65	3195			LT	RADIAL	19/32

18	275/70R18	125/122Q	OWL	33.3	11.1	80	3640			LT	RADIAL	19/32
17	255/65R17	114/110Q	OWL	30.1	10.6	65	2601			LT	RADIAL	20/32
18	275/65R18	123/120M	OWL	32.1	11	80	3415			LT	RADIAL	20/32
18	325/60R18	124/121Q	OWL	33.3	12.9	65	3525			LT	RADIAL	20/32
17	265/70R17	121/118Q	OWL	31.8	10.6	80	3195			LT	RADIAL	19/32
16	315/75R16	121Q	OWL	34.6	12.8	50	3195			LT	RADIAL	19/32
18	275/65R18	119/116Q	OWL	32.1	11	65	3000			LT	RADIAL	20/32
17	235/80R17	120/117Q	OWL	31.9	9.4	80	3042			LT	RADIAL	19/32
18	285/75R18	129/126P	OWL	35.1	11.5	80	4080			LT	RADIAL	19/32
18	275/65R18	119/116Q	OWL	32.1	11	65	3000			LT	RADIAL	20/32
15	33X12.50R15	108Q	OWL	32.9	12.7	35	2205			LT	RADIAL	21/32
16	265/75R16	119/116Q	OWL	31.8	10.8	65	3000			LT	RADIAL	19/32
17	265/70R17	118/115Q	OWL	31.8	10.8	65	2910			LT	RADIAL	19/32
18	285/75R18	129/126P	OWL	35.1	11.5	80	4080			LT	RADIAL	19/32
18	275/70R18	125/122Q	OWL	33.3	11.1	80	3640			LT	RADIAL	19/32
15	30X9.50R15	104Q	OWL	29.9	9.7	50	1984			LT	RADIAL	20/32
15	31X10.50R15	109Q	OWL	30.6	11	50	2270			LT	RADIAL	21/32
15	35X12.50R15	113Q	OWL	34.6	13	35	2535			LT	RADIAL	21/32
17	305/70R17	119/116N	OWL	34	12.2	50	3000			LT	RADIAL	21/32
16	275/70R16	112/109Q	OWL	31.3	11.1	50	2469			LT	RADIAL	19/32
16	265/75R16	112/109Q	OWL	31.8	10.8	50	2469			LT	RADIAL	19/32
17	35X12.50R17	119Q	OWL	35	12.7	50	3000			LT	RADIAL	21/32
18	325/65R18	127/124Q	OBL	34.6	12.8	65	3860			LT	RADIAL	21/32
18	325/65R18	127/124Q	OBL	34.6	12.8	65	3860			LT	RADIAL	21/32
17	245/70R17	114/110Q	OWL	30.8	9.7	65	2601			LT	RADIAL	19/32

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

for Maxxis Tyres | PK
MAXXIS[®] fe
 CEO | Maxxis Pakistan

