

Introducing the new and improved Buckshot Mudder

Aggressive talon-shaped tread elements provide excellent performance in muddy and rocky conditions



SPECIFICATIONS

| Rim Size | Size | Service Description | SideWall Name | Overall Diameter | Section Width | MaxPSI | Max Load [lbs] | Approved Rim Width [in] | Ply Rating | P/C/LT | Radial/Bias | Tread Depth |
|----------|--------------|---------------------|---------------|------------------|---------------|--------|----------------|-------------------------|------------|--------|-------------|-------------|
| 15 | 235/75R15 | 104/101Q | RBL | 29 | 9.4 | 50 | 1985 | | | LT | RADIAL | 18/32 |
| 17 | 285/75 R17 | 121/118Q | RBL | 34.2 | 11.8 | 80 | 3195 | | | LT | RADIAL | 19/32 |
| 20 | 35X12.50R20 | 121Q | RBL | 35 | 12 | 65 | 3195 | | | LT | RADIAL | 20/32 |
| 16 | 305/70 R16 | 124/121Q | RBL | 33 | 12.3 | 65 | 3525 | | | LT | RADIAL | 18/32 |
| 22 | 37X13.50R22 | 123Q | RBL | 37.1 | 13.5 | 65 | 3415 | | | LT | RADIAL | 20/32 |
| 18 | 275/65R18 | 123/120Q | RBL | 32.3 | 11 | 80 | 3415 | | | LT | RADIAL | 19/32 |
| 15 | 35X12.50 R15 | 113Q | RBL | 35 | 13.1 | 35 | 2535 | | | LT | RADIAL | 20/32 |
| 16 | 235/85R16 | 120/116Q | RBL | 31.8 | 9.4 | 80 | 3042 | | | LT | RADIAL | 18/32 |
| 18 | 275/65R18 | 119/116Q | RBL | 32.2 | 11 | 65 | 3000 | | | LT | RADIAL | 19/32 |
| 17 | 265/70R17 | 121/118Q | RBL | 32 | 10.6 | 80 | 3195 | | | LT | RADIAL | 19/32 |
| 18 | 35X12.50R18 | 123Q | RBL | 35 | 12.6 | 65 | 3415 | | | LT | RADIAL | 20/32 |
| 17 | 265/70R17 | 118/115Q | RBL | 31.9 | 10.5 | 65 | 2910 | | | LT | RADIAL | 19/32 |
| 20 | 37X13.50R20 | 127Q | RBL | 36.8 | 13.4 | 65 | 3860 | | | LT | RADIAL | 20/32 |
| 16 | 285/75R16 | 126/123Q | RBL | 33.2 | 11.4 | 80 | 3750 | | | LT | RADIAL | 19/32 |

| | | | | | | | | | | | | |
|----|-----------------|----------|-----|------|------|----|------|--|--|----|--------|-------|
| 17 | 285/70R17 | 121/118Q | RBL | 32.7 | 11.4 | 80 | 3195 | | | LT | RADIAL | 19/32 |
| 17 | 305/70 R17 | 121/118Q | RBL | 34 | 12.3 | 65 | 3195 | | | LT | RADIAL | 18/32 |
| 15 | 31X10.50R15 | 109Q | RBL | 30.6 | 11.1 | 50 | 2270 | | | LT | RADIAL | 19/32 |
| 16 | 315/75 R16 | 127/124Q | RBL | 34.9 | 12.8 | 65 | 3860 | | | LT | RADIAL | 19/32 |
| 16 | 245/75R16 | 120/116Q | RBL | 30.8 | 10.1 | 80 | 3042 | | | LT | RADIAL | 19/32 |
| 16 | 265/75R16 | 123/120Q | RBL | 32 | 10.7 | 80 | 3415 | | | LT | RADIAL | 19/32 |
| 20 | 275/65R20 | 126/123Q | RBL | 34.6 | 11 | 80 | 3750 | | | LT | RADIAL | 19/32 |
| 17 | 35X12.50R17 | 121Q | RBL | 35 | 12.9 | 65 | 3195 | | | LT | RADIAL | 20/32 |
| 16 | 265/75R16 | 112/109Q | RBL | 32 | 10.7 | 50 | 2469 | | | LT | RADIAL | 19/32 |
| 17 | 265/70R17 | 112/109Q | RBL | 31.9 | 10.5 | 50 | 2469 | | | LT | RADIAL | 19/32 |
| 16 | 245/75R16 | 108/104Q | RBL | 30.8 | 10.1 | 50 | 2205 | | | LT | RADIAL | 19/32 |
| 22 | 35X12.50R22 | 117Q | RBL | 35.2 | 12.1 | 65 | 2835 | | | LT | RADIAL | 20/32 |
| 15 | 33X12.50R15 | 108Q | RBL | 33 | 13 | 35 | 2205 | | | LT | RADIAL | 19/32 |
| 1 | 285/70R1 | 127/124Q | RBL | 34.1 | 11.4 | 80 | 3860 | | | LT | RADIAL | 19/32 |
| 20 | 33X12.50R20 | 114Q | RBL | 33 | 12 | 65 | 2600 | | | LT | RADIAL | 19/32 |
| 15 | 30X9.50R15 | 104Q | RBL | 29.7 | 9.8 | 50 | 1985 | | | LT | RADIAL | 18/32 |
| 14 | 27X8.50R14 | 95Q | RBL | 26.6 | 8.8 | 50 | 1520 | | | LT | RADIAL | 18/32 |
| 15 | 32X11.50R15 | 113Q | RBL | 32 | 11.8 | 50 | 2535 | | | LT | RADIAL | 19/32 |
| 17 | 37X13.50 R17 | 121Q | RBL | 30.7 | 10.6 | 65 | 3195 | | | LT | RADIAL | 20/32 |

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

for Maxxis Tyres | PK
MAXXIS[®] fe
 CEO | Maxxis Pakistan

A handwritten signature in blue ink is written over a circular blue stamp. The stamp contains the text "AKESHA HARRIAM PVT. LTD." around the perimeter and "Faisalabad" in the center.