

MAXXCROSS SM

http://maxxis.pk Generated By: MAXXIS.PK

Don't get stuck in the mud or buried in the sand: Pin it and win it with a pair of Maxxcross SM tires.

The SM is an exclusive sand and mud tire that combines a mud-repelling, silica-based rubber compound with a computerenhanced tread design. In addition to its specially formulated compound, the SM tire also incorporates anti-flex knob bridges on the shoulder, increasing traction and stability. The Maxxcross SM is frequently used by Maxxis' top pros when race conditions are sandy or sloppy.



SPECIFICATIONS

Rim Size	Size	Service Description	SideWall Name	Overall Diameter	Section Width	MaxPSI	Max Load [lbs]	Approved Rim Width [in]	Ply Rating	P/C/LT	Radial/Bias	Tread Depth
18	120/100-18	68M TT	Rear	27.4	5.4	32		2.50X18		Р	BIAS	21/32
18	110/100-18	64M TT	Rear	27	5	32		2.15X18		Р	BIAS	21/32
19	100/90-19	57M TT	Rear	26.6	4.4	32		1.85X19		Р	BIAS	20/32
19	110/90-19	62M TT	Rear	27.2	5	32		2.15X19		Р	BIAS	21/32
19	120/90-19	66M TT	Rear	27.5	5.2	32		2.15X19		Р	BIAS	22/32
21	80/100-21	51M TT	FRONT	28.2	3.5	32		1.60X21		Р	BIAS	17/32

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)



