


Xtreme Summer tire designed for drivers who want it all. The VR-1 features a compound that gets up to operating temperatures quickly and provides tenacious dry traction on the street or during competition. The engineers also made sure the compound heat-cycled well so the tire stays fast throughout the life of the tire. The new pattern was designed to maximize dry performance while minimizing white knuckle moments under wet weather. UTQG 200 AA A



## SPECIFICATIONS

Rim Size	Size	Service Description	SideWall Name	Overall Diameter	Section Width	MaxPSI	Max Load [lbs]	Approved Rim Width [in]	Ply Rating	P/C/LT	Radial/Bias	Tread Depth
15	205/50R15	86W	S1	23.1	8.4	51	1168	NA		P	RADIAL	9/32
16	205/55R16	91V	S1	24.8	8.3	51	1356	NA		P	RADIAL	9/32
17	255/40R17	94W	S2	25	10.2	51	1477	NA		P	RADIAL	9/32
18	255/35R18	94W XL	S2	25	10.39	50	1477	NA		P	RADIAL	9/32
18	225/40R18	88W	S2	25.2	9.1	51	1235	NA		P	RADIAL	9/32
15	245/40R15	88W	S2	22.7	9.8	51	1235	NA		P	RADIAL	9/32
18	245/40R18	93W	S2	25.7	9.7	51	1433	NA		P	RADIAL	9/32
15	205/50R15	86W	S2	23.1	8.4	51	1168	NA		P	RADIAL	9/32
15	225/45R15	87W	S2	23	8.8	51	1202	NA		P	RADIAL	9/32
18	295/40R18	103W	S2	27.4	11.9	51	1929	NA		P	RADIAL	9/32
17	215/40R17	83W	S2	23.7	8.6	51	1074	NA		P	RADIAL	9/32
18	295/40R18	103W	S1	27.4	11.9	51	1929	NA		P	RADIAL	9/32
17	245/40R17	95W XL	S2	24.7	9.69	50	1521	NA		P	RADIAL	9/32
18	265/35R18	97W XL	S2	25.5	10.8	50	1609	NA		P	RADIAL	9/32
16	215/40R16	86W XL	S2	22.8	8.62	50	1169	NA		P	RADIAL	6/32
17	225/45R17	94W XL	S2	25.2	8.9	50	1477	NA		P	RADIAL	9/32



Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

for Maxxis Tyres | PK  
**MAXXIS**<sup>®</sup>  
CEO | Maxxis Pakistan

A handwritten signature in blue ink is written over a circular blue stamp. The stamp contains the text "AKESHA HARRIAN PVT. LTD." around the perimeter and "Faisalabad" in the center.