

Continuous centre rib design improves braking and high-speed performance

Reinforced shoulder blocks reduce deformation under cornering for improved handling, traction, and steering precision



## SPECIFICATIONS

Rim Size	Size	Service Description	SideWall Name	Overall Diameter	Section Width	MaxPSI	Max Load [lbs]	Approved Rim Width [in]	Ply Rating	P/C/LT	Radial/Bias	Tread Depth
19	275/40R19	105Y XL	BSW	27.7	10.8	50	1819	9.5		P	RADIAL	11/32
18	255/35R18	94Y XL	BSW	25	10	50	1477	9		P	RADIAL	10/32
17	215/45R17	91Y XL	BSW	24.6	8.5	50	1356	7		P	RADIAL	11/32
18	225/40R18	92Y XL	BSW	25	8.9	50	1389	8		P	RADIAL	11/32
18	245/45R18	100Y XL	BSW	26.6	9.6	50	1764	8		P	RADIAL	11/32
19	225/35R19	88Y XL	BSW	25.2	8.9	50	1235	8		P	RADIAL	10/32
18	265/40R18	101Y XL	BSW	26.3	10.4	50	1609	9.5		P	RADIAL	11/32
19	245/40R19	98Y XL	BSW	26.7	9.6	50	1477	8.5		P	RADIAL	11/32
17	205/45R17	88W XL	BSW	24.3	8.1	50	1235	7		P	RADIAL	11/32
18	215/45R18	93Y XL	BSW	25.6	8.5	50	1433	7		P	RADIAL	11/32
16	215/40R16	86W XL	BSW	22.8	8.5	50	1168	7.5		P	RADIAL	11/32
17	205/50R17	93Y XL	BSW	25.1	8.1	50	1433	6.5		P	RADIAL	11/32
18	245/40R18	97Y XL	BSW	25.8	9.6	50	1609	8.5		P	RADIAL	11/32
18	215/35R18	84Y XL	BSW	24	8.5	50	1102	7.5		P	RADIAL	10/32
19	245/35R19	93Y XL	BSW	25.8	9.6	50	1433	8.5		P	RADIAL	10/32
19	235/35R19	91Y XL	BSW	25.5	9.3	50	1356	8.5		P	RADIAL	10/32

17	235/45R17	97Y XL	BSW	25.4	9.3	50	1609	8		P	RADIAL	11/32
19	255/40R19	100Y XL	BSW	27	10	50	1764	9		P	RADIAL	11/32
17	245/40R17	95Y XL	BSW	24.7	9.6	50	1356	8.5		P	RADIAL	11/32
18	235/40R18	95Y XL	BSW	25.4	9.3	50	1521	8.5		P	RADIAL	11/32
18	245/35R18	92Y XL	BSW	24.8	9.6	50	1389	8.5		P	RADIAL	10/32
19	245/45R19	102Y XL	BSW	27.7	9.6	50	1874	8		P	RADIAL	11/32
16	205/55R16	94W XL	BSW	24.9	8.1	50	1477	6.5		P	RADIAL	11/32
16	215/55R16	97W XL	BSW	25.3	8.5	50	1609	7		P	RADIAL	11/32
17	245/45R17	99W XL	BSW	25.7	9.6	50	1709	8		P	RADIAL	11/32
18	225/45R18	95Y XL	BSW	25.9	8.9	50	1521	7.5		P	RADIAL	11/32
18	275/45R18	107Y XL	BSW	27.8	10.8	50	2149	9		P	RADIAL	11/32
17	205/40R17	84W XL	BSW	23.5	8.1	50	1102	7.5		P	RADIAL	11/32
17	225/45R17	94Y XL	BSW	24.8	8.9	50	1477	7.5		P	RADIAL	11/32
19	255/45R19	104Y XL	BSW	28.1	10	50	1984	8.5		P	RADIAL	11/32
18	225/35R18	87Y XL	BSW	24.3	8.9	50	1201	8		P	RADIAL	10/32
16	205/45R16	87W XL	BSW	23.1	8.1	50	1201	7		P	RADIAL	11/32
18	235/45R18	98Y XL	BSW	26.3	9.3	50	1477	8		P	RADIAL	11/32

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

for Maxxis Tyres | PK  
**MAXXIS®**  
 CEO | Maxxis Pakistan

A handwritten signature in blue ink is written over a circular blue stamp. The stamp contains the text "AKESHA HARRIAM PVT. LTD." around the perimeter and "Faisalabad" in the center.