

Designed For European commercial vehicles, the vansmart MCV5 improves upon the already successful MCV5 while also reducing rolling resistance.

The MCV5 uses a new silica compound to minimize rolling resistance and improve wet traction, while the new bead filler improves overall durability and ride comfort.



SPECIFICATIONS

Rim Size	Size	Service Description	Side wall	Overall Diameter	Section Width	MAX (PSI)	Max Load (lbs)	Approved Rim Width	Ply Rating	P/C/LT	Radial/Bias	Tread Depth
12	155R12C	88/86R 8PR	BSW	21.8	6.3	65	S1235/D1170	4.5		C	Radial	10/32
12	LT5.00R12	83/81P 8PR	BSW	22.3	5.3	65	S1070/D1025	3.5		LT	Radial	11/32
12	LT5.50R12	92/90P 10PR	BSW	23.4	6.4	73	51390/D1325	4		LT	Radial	11/32
12	145R12C	86/84N 8PR	BSW	21.3	5.6	65	51170/D1100	4		C	Radial	10/32
13	165R13C	94/93R 8PR	BSW	23.5	6.6	65	51475/D1435	4.5		C	Radial	11/32
13	155R13C	91/89N 8PR	BSW	22.8	6.1	65	51355/D1280	4.5		C	Radial	10/32
13	175R13C	97/95N 8PR	BSW	24.1	7	65	51610/D1520	5		C	Radial	11/32
13	LT5.50R13	97/95P 12PR	BSW	24.5	6.4	91	51610/D1520	4		LT	Radial	11/32
14	195R14C	106/104R 8PR	BSW	26.3	7.8	65	52095/D1985	5.5		C	Radial	12/32
14	185R14C	102/100R 8PR	BSW	25.6	7.5	65	51875/D1765	5.5		C	Radial	11/32
14	205R14C	109/107Q 8PR	BSW	27	8.3	65	S2270/D2150	6		C	Radial	12/32
14	165 R14C	97/95N 8PR	BSW	24.5	6.7	65	51610/D1520	5		C	Radial	11/32
14	175R14C	99/98Q 8PR	BSW	25	7	65	51710/D1655	5		C	Radial	11/32
15	195R15C	106/104R 8PR	BSW	27.1	7.9	65	52095/D1985	5.5		C	Radial	12/32
15	205/70R15C	106/104R 8PR	BSW	26.5	8.1	65	52095/D1985	6		C	Radial	12/32
15	215/70R15C	109/107S 8PR	BSW	27	8.7	65	52270/D2150	6.5		C	Radial	12/32
15	225/70R15C	112/110S 8PR	BSW	27.6	8.8	65	52470/D2335	6.5		C	Radial	12/32
16	195/75R16C	107/105R 8PR	BSW	27.2	7.7	69	52150/D2040	5.5		C	Radial	12/32
16	215/75R16C	113/111S 8PR	BSW	28.4	8.4	69	52535/D2405	6		C	Radial	12/32
16	205/75R16C	110/108R 8PR	BSW	27.9	7.8	69	52335/D2205	5.5		C	Radial	12/32
16	215/65R16C	109/107T 8PR	BSW	27.2	8.5	69	52270/D2150	6.5		C	Radial	12/32

16	225/75R16C	121/120R 10PR	BSW	29	8.6	84	S3195/D3085	6		C	Radial	12/32
16	215/70R16C	108/106T 8PR	BSW	27.9	8.6	54	52205/D2095	6.5		C	Radial	12/32

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

for Maxxis Tyres | PK

MAXXIS[®]

CEO | Maxxis Pakistan

A handwritten signature in blue ink is written over a circular blue stamp. The stamp contains the text "AKESHA HARRIAN (PVT) LTD." around the perimeter and "Faisalabad" in the center.